



Fujian Zhenyuan Hydraulic Equipment C...



1204 ETN9/C3 Bearing 2D drawings and 3D CAD models

SKF 1204 ETN9/C3 Self Aligning Ball Bearings

Bearing No. 1204 ETN9/C3

| | |
|-------------------------|---|
| Category | Self Aligning Ball Bearings |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.119 |
| EAN | 7316576620508 |
| Product Group | B00152 |
| Mounting Method | Shaft |
| Enclosure | Open |
| Rolling Element | Ball Bearing |
| Cage Material | Polyamide |
| Precision Class | ABEC 1 ISO P0 |
| Internal Clearance | C3-Loose |
| Number of Rows of Balls | Double Row |
| Other Features | Allowable Misalignment 2.5 Deg High Capacity Design |
| Long Description | 20MM Bore; Shaft Mount; 47MM Outside Diameter; 14MM Inner Race Width; 14MM Outer Race Width; Open; Polyamide Cage; Double Row of Balls; ABEC 1 ISO P0; C3-Loose |
| Inch - Metric | Metric |
| Category | Self Aligning Ball Bearings |
| UNSPSC | 31171532 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| | |



Fujian Zhenyuan Hydraulic Equipment C...

| Keyword String | Self Aligning |
|--------------------------|---|
| Manufacturer URL | http://www.skf.com |
| Manufacturer Item Number | 1204 ETN9/C3 |
| Weight / LBS | 0.262 |
| Inner Race Width | 0.551 Inch 14 Millimeter |
| d | 0.787 Inch 20 Millimeter |
| Outer Race Width | 0.551 Inch 14 Millimeter |
| D | 1.85 Inch 47 Millimeter |
| bore diameter: | 20 mm |
| precision rating: | Not Rated |
| outside diameter: | 47 mm |
| maximum rpm: | 20000 RPM |
| overall width: | 14 mm |
| cage material: | Fiberglass Reinforced Nylon |
| bore type: | Straight |
| finish/coating: | Uncoated |
| closure type: | Open |
| maximum misalignment: | 2.5 ° |
| internal clearance: | C3 |
| outer ring width: | 14 mm |
| dynamic load capacity: | 12.7 kN |
| fillet radius: | 1 mm |
| static load capacity: | 3.4 kN |
| series: | 1200 |